














Item	Colour coded according to EN1492-2	Working Load Limit with 1 round sling							Working Load Limit with 2 round slings			
		Straight lift	Choked lift	0-7	$\beta$				Straight lift up to 45	Choked lift up to 45	Straight lift 45-60	Choked lift 45-60
					0-7	7-45	45-60	45-60				
												
1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.12	1.0	0.8		
DSRES-1T	WLL 1T	1.000	800	2.000	1.400	1.000	700	500	1.400	1.120	1.000	800
DSRES-2T	WLL 2T	2.000	1.600	4.000	2.800	2.000	1.400	1.000	2.800	2.240	2.000	1.600
DSRES-3T	WLL 3T	3.000	2.400	6.000	4.200	3.000	2.100	1.500	4.200	3.360	3.000	2.400
DSRES-4T	WLL 4T	4.000	3.200	8.000	5.600	4.000	2.800	2.000	5.600	4.480	4.000	3.200
DSRES-5T	WLL 5T	5.000	4.000	10.000	7.000	5.000	3.500	2.500	7.000	5.600	5.000	4.000
DSRES-6T	WLL 6T	6.000	4.800	12.000	8.400	6.000	4.200	3.000	8.400	6.720	6.000	4.800
DSRES-8T	WLL 8T	8.000	6.400	16.000	11.200	8.000	5.600	4.000	11.200	8.960	8.000	6.400
DSRES-10T	WLL 10T	10.000	8.000	20.000	14.000	10.000	7.000	5.000	14.000	11.200	10.000	8.000
DSRES-12T	WLL 12T	12.000	9.600	24.000	16.800	12.000	8.400	6.000	16.800	13.400	12.000	9.600